

The latex-lab-toc-hyperref-changes package

Changes and additions to hyperref related to toc entries

L^AT_EX Project*
v0.85a 2023-07-20

Abstract

1 Introduction

The followings contains various change needed for hyperref for the new toc tagging code. They should be only loaded if hyperref is used!

```
1 <*package>
```

2 Changes for hyperref

2.1 \contentsline,\addcontentsline

The standard \contentsline and \addcontentsline should also be used with hyperref (together with more changes below) so we have to disable the redefinition in hyperref (this requires hyperref version 7.00v!

```
2 \def\hyper@nopatch@toc{}
3 \AddToHook{package/hyperref/after}
4 {
5   \@ifpackagelater{hyperref}{2023-02-07}{}
6   {\PackageWarning{latex-lab-testphase-toc-tagging}{hyperref too old}{}
7   }
```

2.2 Add links to toc entries

```
8 \ExplSyntaxOn
9 \AddToHook{package/hyperref/after}
10 {
11   \AddToHookWithArguments{contentsline/text/before}[hyp]
12   {
13     \tl_if_blank:nF {#2}%text
14     {
15       \tl_if_blank:nF {#4}%destination
16       {
17         \int_case:nnF {\Hy@linktoc}
```

*Initial implementation done by Ulrike Fischer

```

18         {
19             {0}{} %none
20             {1}{\hyper@linkstart{link}{#4}} %section
21             {2}{} %page
22         }
23         {\hyper@linkstart{link}{#4}} %all
24     }
25 }
26 }
27 \AddToHookWithArguments{contentsline/text/after}[hyp]
28 {
29     \tl_if_blank:nF {#2}
30     {
31         \tl_if_blank:nF {#4}
32         {
33             \int_case:nnF {\Hy@linktoc}
34             {
35                 {0}{} %none
36                 {1}{\hyper@linkend} %section
37                 {2}{} %page
38             }
39             {\hyper@linkend} %all
40         } % none
41     }
42 }
43
44 \AddToHookWithArguments{contentsline/page/before}[hyp]
45 {
46     \tl_if_blank:nF {#3}
47     {
48         \tl_if_blank:nF {#4} %
49         {
50             \int_case:nnF {\Hy@linktoc}
51             {
52                 {0}{} %none
53                 {1}{} %section
54                 {2}{\hyper@linkstart{link}{#4}} %page
55             }
56             {\hyper@linkstart{link}{#4}} %all
57         } % none
58     }
59 }
60 \AddToHookWithArguments{contentsline/page/after}[hyp]
61 {
62     \tl_if_blank:nF {#3}
63     {
64         \tl_if_blank:nF {#4}
65         {
66             \int_case:nnF {\Hy@linktoc}
67             {
68                 {0}{} %none
69                 {1}{} %section
70                 {2}{\hyper@linkend} %page
71             }

```

```

72             {\hyper@linkend} %all
73         } % none
74     }
75 }
76 \AddToHookWithArguments{cmd/addcontentsline/before}[hyp]
77 {%
78     \Hy@addcontentsline@addbookmark
79     {#1}
80     {#2}
81     {#3}%
82 }
83 }
84 \ExplSyntaxOff

```

2.3 Add bookmark code to \addcontentsline

```

85 \newcommand\Hy@addcontentsline@addbookmark[3]{%#1 toc type, #2 level, #3 content
86     {%
87         \ifx\@currentHref\@empty
88             \Hy@Warning{%
89                 No destination for bookmark of \string\addcontentsline,%
90                 \MessageBreak destination is added%
91             }%
92             \phantomsection
93         \fi
94         \begingroup
95         \expandafter\ifx\csname toplevel@#2\endcsname\relax
96             \begingroup
97             \def\Hy@tempa{#1}%
98             \ifx\Hy@tempa\Hy@bookmarkstype
99                 \Hy@WarningNoLine{%
100                     bookmark level for unknown #2 defaults to 0%
101                 }%
102             \else
103                 \Hy@Info{bookmark level for unknown #2 defaults to 0}%
104             \fi
105         \endgroup
106         \expandafter\gdef\csname toplevel@#2\endcsname{0}%
107         \fi
108         \edef\Hy@toplevel{\csname toplevel@#2\endcsname}%
109         \Hy@writebookmark{\csname the#2\endcsname}%
110             {#3}%
111             {\@currentHref}%
112             {\Hy@toplevel}%
113             {#1}%
114         \ifHy@verbose
115             \begingroup
116             \def\Hy@tempa{#3}%
117             \@onelevel@sanitize\Hy@tempa
118             \let\temp@online\on@line
119             \let\on@line\@empty
120             \Hy@Info{%
121                 bookmark\temp@online:\MessageBreak
122                 thecounter {\csname the#2\endcsname}\MessageBreak
123                 text {\Hy@tempa}\MessageBreak

```

```

124         reference {\@currentHref}\MessageBreak
125         toplevel {\Hy@toclevel}\MessageBreak
126         type {#1}%
127     }%
128 \endgroup
129 \fi
130 \endgroup
131 }
132 \end{package}

```